Oxygen & Argon Works Ltd.	Spec.No.G-02.001	
Product Manufacturing Control	Issue: D	Date:14.02.2008
GAS SPECIFICATION	Sheet 1 of 1	-

<u>NITROGEN - Dry - 99.99%</u>

Typical Impurity Limits:

Oxygen: $\leq 50 \text{ ppm}$ Moisture: $\leq 10 \text{ ppm}$ T.H.C. $\leq 7 \text{ ppm}$ Carbon dioxide: $\leq 3 \text{ ppm}$

Above specification applies to both Nitrogen Gas and Nitrogen Liquid.

Quality Assurance - According to company QC procedure No. 02.01.

Manufacture - According to Company Works' Instructions Nos:. 01.01, 01.02, 01.03, 02.01.

Packing & Distribution -

In high pressure gas cylinders, liquid DEWARS and Cryogenic road tankers according to customers' requirements.

Valve Outlet Thread - According to IS 637 part 3.

[21.7mm Whitworth, 14 teeth/", Male, Cylindrical, right hand]



Hazardous Materials Codes				
	U.N. No.	Emergency Actions	Hazard Class	
GAS	1066	2T	2.2	
LIQUID	1977	2T	2.2	

O M. D. II	D : 14.00.0000	0:	10.1
Originator: Meir Ben Ishay	Date: 14.02.2008	Signature:	
			