Oxygen & Argon Works Ltd.	Spec.No.G-01.004	
Product Manufacturing Control	Issue: C	Date:14.02.2008
GAS SPECIFICATION	Sheet 1 of 1	

OXYGEN - High Purities - 99.7% / 99.8%

Typical Impurity Limits:

Grade:	99.7%	99.8%	
Argon + Inerts:	≤ 0.3%	≤ 0.2%	
Moisture:	≤ 2 ppm	≤2 ppm	
T.H.C.	≤ 15 ppm	≤ 15 ppm	

Above specification applies to both Oxygen Gas and Oxygen Liquid.

Quality Assurance - According to company QC procedure No. 01.04.

Manufacture - According to Company Works' Instructions Nos.: 01.01, 01.02, 02.01.

Packing & Distribution -

In high pressure gas cylinders, liquid DEWARS and Cryogenic road tankers according to customers'

requirements.

Valve Outlet Thread - According to IS 607 part 3.

[¾" BSP, 14 teeth/", Male, Cylindrical, right hand]

	Hazardous M	aterials Codes		
	U.N. No.	Emergency Actions	Hazard Class	
GAS	1072	2S	2.2, 5.1	
LIQUID	1073	2P	2.2, 5.1	77 77
			7	ראיובור ויציה בה

